

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
11 March 2004 (11.03.2004)

PCT

(10) International Publication Number
WO 2004/020957 A1

(51) International Patent Classification⁷:
G01P 5/04

G01F 1/28,

(74) Agent: CURO AS; Box 38, N-7231 Lundamo (NO).

(21) International Application Number:

PCT/NO2003/000244

(22) International Filing Date: 10 July 2003 (10.07.2003)

(25) Filing Language:

Norwegian

(26) Publication Language:

English

(30) Priority Data:

20024089

27 August 2002 (27.08.2002)

NO

(71) Applicant (for all designated States except US): **CORRO-CEAN ASA** [NO/NO]; Teglgaarden, N-7485 Trondheim (NO).

(72) Inventor; and

(75) Inventor/Applicant (for US only): **BRAATEN, Nils, Arne** [NO/NO]; Kronprins Olavs Allè 22, N-7030 Trondheim (NO).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

- with international search report
- with amended claims

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: FLOW MEASURING METHOD AND DEVICE



(57) Abstract: Flow measuring method and device for measuring the velocity of a single-phase or multi-phase flow, such as a multi-phase flow in a process pipe etc. The method comprises calculating the flow velocity U only by measuring consecutive values of pressure p , temperature T and momentum D , and then calculating the change in pressure Δp , change in temperature ΔT and change in momentum ΔD . The device comprises a probe (1) with a housing (2) comprising electronic components connected to different sensors in the probe (1). The probe comprises a long, hollow momentum tube (3), fastened by its first end (3A) to the housing (2) and a hollow, cylindrical sensor tube (4), located inside the momentum tube (3) fastened by its first end (4A) to the first end (3A) of the momentum tube (3). The sensor tube (4) comprises plate capacitors (CA1, CA2, CA3, CA4) located on the outside of the second end (B) of the momentum tube (3), thereby being able to measure the conductance between the momentum tube (3) and the plate capacitors (CA1, CA2, CA3, CA4) on the sensing tube (4). The probe comprises a pressure sensor and a temperature sensor.